

## CLAIMS:

1. A method of channel estimation in a cellular communication system in which symbols are transmitted between a mobile station and a base station, the method comprising:
- receiving via a communication channel an incoming signal;
  - providing a first estimate for the channel impulse response of that communication channel and utilising that first estimate to process the incoming signal to generate an estimated data symbol;
  - using said estimated data symbol to generate a soft output feedback decision; and
  - using the soft output feedback decision to make a further estimate of the channel impulse response.
2. A method according to claim 1, wherein the incoming signal incorporates symbols spread by a spreading code in a CDMA system.
3. A method according to claim 2, wherein the channel impulse response is estimated by performing a correlation process between a conjugate version of the spreading code and the incoming signal, and multiplying the results of that process by the soft feedback decision value as a weighting value for the channel impulse response.
4. A method according to any preceding claim, wherein the incoming signal includes data symbols and pilot symbols, a unique spreading code having been used respectively for pilot symbols and data symbols.
5. A method according to claim 2 or 4, in which a long spreading code has additionally been used to spread the symbols prior to transmission.
6. A method of channel estimation in a cellular communication system in which symbols are transmitted between a mobile station and a base station, the method comprising:

105THO-044901

95

receiving via a communication channel an incoming signal which incorporates symbols spread by a spreading code;

providing a first estimate for the channel impulse response of that communication channel and utilising that first estimate to process the incoming signal to generate an estimated data symbol;

making a further estimate of the channel impulse response by performing a correlation process between a conjugate version of the spreading code and the incoming signal, and multiplying the results of that process by a feedback decision based on said estimated data symbol as a weighting value for the channel impulse response.

7. A method according to claim 6, wherein the feedback decision is a soft output.

8. A method according to claim 6, wherein the feedback decision is a hard output.

9. Circuitry for estimating a channel impulse response in a cellular communication system in which symbols are transmitted between a mobile station and a base station, the circuitry comprising:

a receiver for receiving via a communication channel an incoming signal which incorporates symbols spread by a spreading code;

a channel impulse response generator for providing a first estimate for the channel impulse response of that communication channel;

a data symbol generator for generating an estimated data symbol using the first estimate of the channel impulse response;

circuitry for providing a further estimate of the channel impulse response by performing a correlation process between a conjugate version of the spreading code and the incoming signal, and multiplying the results of that process by a feedback decision based on said estimated data symbol as a weighting value for the further estimate of the channel impulse response.

09838810-041903

wherein the soft output feedback decision is used to make a further estimate of the channel impulse response.